

LOC/DME I-GKY <u>111.55</u> Chan 52 (Y)	APP CRS 342°	Rwy Ldg 6080 TDZE 620 Apt Elev 628
---	------------------------	---

ILS or LOC/DME RWY 34
ARLINGTON MUNI (GKY)

▼ When local altimeter setting not received, use Grand Prairie
▲ Muni altimeter setting. Inop table does not apply to S-ILS 34.
▲ For inop MALSR increase S-LOC 34 Cat A, B visibility to 1 mile.



MISSED APPROACH: Climb to 1100 then climbing left turn to 3000 via heading 245° and TTT VOR/DME R-206 to TILLA INT/TTT 37 DME and hold.

ASOS 127.375	LONE STAR APP CON 135.975 379.9	ARLINGTON TOWER ★ 128.625 (CTAF) 0	GND CON 121.875	CLNC DEL 121.875	CLNC DEL 118.85 (When twr closed)
------------------------	---	--	---------------------------	----------------------------	--

RADAR REQUIRED

LOCALIZER 111.55
I-GKY 
Chgn 52(Y)

I-GKY 5.
RADAR

(IF)
ESIKE
KY 11.4
RADAR

(IAF)
WIKED
GKY 16.4
RADAR

MSA TTI 25 NM

2700

$90^\circ \rightarrow$ $\leftarrow 270^\circ$

3600

ELEV	628		TDZE	620
------	-----	--	------	-----

1100 ↑	3000 hdg 245°	TTT R-206	TILLA △
-----------	---------------------	--------------	------------

*LOC only.

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 55). 53145

MYKES
I-GKY 54

ESIKE
I-GKY 11.4
RADAR

I-GKY 2.4

2300

GS 3.00°
TCH 60

☆
TWR

MIRL Rwy 16-34
REIL Rwy 16

CATEGORY	A	B	C	D
S-ILS 34	820- $\frac{3}{4}$	200 (200- $\frac{3}{4}$)		NA
S-LOC 34	1060- $\frac{3}{4}$	440 (500- $\frac{3}{4}$)		NA
CIRCLING	1100-1 472 (500-1)	1140-1 512 (600-1)	1220-1 $\frac{1}{2}$ 592 (600-1 $\frac{1}{2}$)	NA