

WAAS CH 77900 W13A	APP CRS 130°	Rwy Ldg TDZE 1301 Apt Elev 1304
--	------------------------	---

RNAV (GPS) RWY 13

MITCHELL MUNI (MHE)

RNP APCH - GPS.



▼

⚠

Baro-VNAV and VDP NA when using HON altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use HON altimeter setting and increase LPV DA to 1664 feet and all visibilities 1⁄8 SM. Increase LNAV/VNAV DA to 1776 feet and all visibilities 1⁄4 SM. Increase all MDAs 100 feet and LNAV visibility Cat C/D 1⁄4 SM, and Circling visibility Cat C/D 1⁄4 SM.

MISSED APPROACH: Climb to 3200 direct JUTUB and hold.

ASOS 124.175	MINNEAPOLIS CENTER 126.25 339.8	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



4 NM Holding Pattern 6000 ← 310° 3500 → 130° GP 3.00° TCH 46		NUSCI		CUDGA		3200 ↑	JUTUB ✦
		6 NM		4.4 NM		1.4 NM to RW13 RW13	
CATEGORY	A	B	C	D			
LPV DA	1575-1 274 (300-1)						
LNAV/VNAV DA	1687-1¼ 386 (400-1¼)						
LNAV MDA	1780-1 479 (500-1)			1780-1⅓ 479 (500-1⅓)			
CIRCLING	1780-1¼ 476 (500-1¼)			1820-1½ 516 (600-1½)		1880-2 576 (600-2)	