

RNP APCH

⚠

⚠

W

Circling NA for Cat D southwest of Rwy 13-31. When local altimeter setting not received, use Laughlin AFB altimeter setting and increase all DA 30 feet and all MDA 40 feet, increase LPV visibility all Cats, LNAV Cats C and D and Circling Cats C and D visibility ¼ SM. Baro-VNAV NA when using Laughlin AFB altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17° C (2°F) or above 47°C (116°F).

MALS

MISSED APPROACH: Climb to 4000 direct AREXE and on 069° track to DLF VORTAC and hold, continue climb-in-hold to 4000.

ASOS 118.525	DEL RIO APP CON * 119.6 259.1	CLNC DEL 120.5	UNICOM 122.8 (CTAF)
------------------------	---	--------------------------	-------------------------------

ELEV 1002	D	TDZE 1002
-----------	----------	-----------

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 47).				
4 NM		4000	AREXE	tr 069°
Holding Pattern				DLF
← 312° 132° → GP 3.00° TCH 48 2700 2700 1640 8.6 NM 3.2 NM 1.9 * HIBUD 1.9 NM to RW13 * LNAV only.				
CATEGORY	A	B	C	D
LPV DA		1252-¾	250 (300-¾)	
LNAV/VNAV DA		1401-1	399 (400-1)	
LNAV MDA	1500-½ 498 (500-½)		1500-¾ 498 (500-¾)	1500-1 498 (500-1)
CIRCLING	1500-1 498 (500-1)	1560-1 558 (600-1)	1740-2 738 (800-2)	1740-2½ 738 (800-2½)

DEL RIO, TEXAS

Amdt 2B 20MAY21

29°22'N-100°56'W

DEL RIO INTL (DRT)

RNAV (GPS) RWY 13