

LOC/DME I-BFT	APP CRS	Rwy Ldg	24R	24L
109.75	245°	TDZE	6003	5197
Chan 34 (Y)		Apt Elev	583	584
			584	584

ILS or LOC RWY 24R

BURKE LAKEFRONT (BKL)

DME required. RADAR required for procedure entry.


⚠

Circling Rwy 6R NA at night. Rwy 24R helicopter visibility reduction below ¾ SM NA. Circling NA southeast of Rwy 6R-24L. S-ILS minimums NA when control tower closed.

MALSF

MISSED APPROACH: Climb to 1120 then climbing right turn heading 350° and DJB VOR/DME R-056 to cross LLROY/DJB 25.5 DME at or below 2000 then climb to 3000 on DJB VOR/DME R-056 northeast course to NEVTE/DJB 31.1 DME and hold.

ATIS	CLEVELAND APP CON	LAKEFRONT TOWER ★	GND CON	UNICOM
125.25	125.35 346.325	124.3 (CTAF) 0 339.8	121.9 339.8	122.95 0



ELEV 584

D

TDZE 24R 583

TDZE 24L 584

1120

↑

hdg 350°

DJB R-056

LLROY DJB 25.5

2000

3000

NEVTE DJB 31.1

245°

6604 X 150

5197 X 100

TWR

I-BFT 1.1

I-BFT 2.4

TABEY I-BFT 6.7

BOGGE I-BFT 12.7

2400

2400

245°

GS 3.00°

TCH 42

CATEGORY	A	B	C	D
S-ILS 24R	916-3/4 333 (400-3/4)			
S-LOC 24R	1060-3/4	477 (500-3/4)	1060-1 1/8	477 (500-1 1/8)
SIDESTEP 24L	1060-1	476 (500-1)	1060-1 1/2	476 (500-2)
CIRCLING	1060-1	476 (500-1)	1140-1 1/2	1200-2
			556 (600-1 1/2)	616 (700-2)

EC-2, 06 AUG 2026 to 03 SEP 2026

EC-2, 06 AUG 2026 to 03 SEP 2026