

WAAS CH 99701 W24A	APP CRS 240°	Rwy Ldg TDZE 545 Apt Elev 547
--	------------------------	---

RNAV (GPS) RWY 24

MUSCATINE MUNI (MUT)

RNP APCH - GPS.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LPV all Cats visibility to 1 ½ SM, LNAV/VNAV all Cats visibility to 1 ½ SM, and LNAV Cats C/D visibility to 1 ½ SM. When local altimeter setting not received, use IOW altimeter setting and increase LPV DA to 883 feet; increase LNAV/VNAV DA to 1024 feet and all visibilities ¼ SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C ¼ SM. Baro-VNAV and VDP NA when using IOW altimeter setting.

MALSR

MISSED APPROACH:
Climb to 3000 direct
IZBUF and hold.

AWOS-3P 120.625	QUAD CITY APP CON ★ 133.275 257.8	CLNC DEL 119.125	UNICOM 122.7 (CTAF) ①
---------------------------	---	----------------------------	---------------------------------

3000	IZBUF	YELDU 2.1 NM to RW24	JOLIX 2300	EDAGE	5 NM Holding Pattern
1.2 NM	1.2 NM	1 NM	3.2 NM	6 NM	
1260	2300	240°	060°	240°	6000 3100
GP 3.00° TCH 55'					
CATEGORY	A	B	C	D	
LPV DA	812-½	267 (300-½)			
LNAV/VNAV DA	953-¾	408 (500-¾)			
LNAV MDA	960-½	415 (500-½)	960-¾	415 (500-¾)	
CIRCLING	1080-1 533 (600-1)	1200-1 653 (700-1)	1200-1¾ 653 (700-1¾)	1500-3 953 (1000-3)	

ELEV 547 TDZE 545

REIL Rwy 6, 12, and 30 ①
MIRL Rwy 6-24 and 12-30 ①

MUSCATINE, IOWA
Orig-C 14MAY26

41°22'N-91°09'W

MUSCATINE MUNI (MUT)
RNAV (GPS) RWY 24