ATIS
118.325
CLNC DEL
120.45
CLNC DEL
119.55 (when twr closed)
GND CON
120.45
CONROE TOWER ★
124.125 (CTAF)
HOUSTON DEP CON
119.7 281.4

TOP ALTITUDE: ASSIGNED BY ATC



NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

TAKEOFF MINIMUMS
Rwys 1, 14, 19, 32:
Standard with minimum climb of 500' per NM to 760.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 1: Climb on heading 012° to 760 for RADAR vectors to DREMR, thence . . . .
TAKEOFF RUNWAY 14: Climb on heading 140° to 760 for RADAR vectors to DREMR, thence . . . .
TAKEOFF RUNWAY 19: Climb on heading 192° to 760 for RADAR vectors to DREMR, thence . . . .
TAKEOFF RUNWAY 32: Climb on heading 320° to 760 for RADAR vectors to DREMR, thence . . . .

...on track 345° to LITLD, then on track 346° to BLTWY, then on (transition). Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure.

CRIED TRANSITION (BLTWY7.CRIED)

NOTE: Chart not to scale.

SC-5, 06 AUG 2026 to 03 SEP 2026
SC-5, 06 AUG 2026 to 03 SEP 2026