

APP CRS
097°

Rwy Ldg
TDZE
Apt Elev

5190
1113
1136

RNAV (GPS) RWY 10

WAYNE COUNTY (BJJ)

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Akron-Canton Rgnl altimeter setting and increase all MDA 60 feet and visibility Circling Cat C/D ¼ SM.

MISSED APPROACH:
Climb to 3000 direct DEHYYY and hold.

ASOS 118.075	CLEVELAND APP CON ★ 125.5 371.875	CLNC DEL 121.75	UNICOM 122.975 (CTAF) 0
-----------------	--------------------------------------	--------------------	----------------------------

6 NM Holding Pattern

VGSI and descent angles not coincident (VGSI Angle 3.04/TCH 33).

3000 DEHYYY

JAVNE

TONSR

COPAK 2.2 NM to RW10

RW10

1860

2800

3000

277°

097°

3.04° TCH 40

6 NM

2.9 NM

2.2 NM

CATEGORY	A	B	C	D
LNAV MDA	1540-1	427 (500-1)	1540-1¼ 427 (500-1¼)	1540-1½ 427 (500-1½)
CIRCLING	1600-1 464 (500-1)	1700-1 564 (600-1)	1800-1¾ 664 (700-1¾)	1840-2¼ 704 (800-2¼)

REIL Rwy 10 and 28 0
HIRL Rwy 10-28 0

WOOSTER, OHIO

Orig-A 12AUG21

40°52'N-81°53'W

WAYNE COUNTY (BJJ)

RNAV (GPS) RWY 10