

WAAS CH 48916 W35A	APP CRS 351°	Rwy Ldg TDZE 95 Apt Elev 101
--	------------------------	--



RNAV (GPS) RWY 35
LOWCOUNTRY RGNL (RBW)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Charleston AFB/Intl altimeter setting.

⚠ DME/DME RNP-0.3 NA. When local altimeter setting not received, use Charleston AFB/Intl altimeter setting: increase LPV DA to 476 feet and LNAV/VNAV DA to 525 feet and all MDA 80 feet; increase LPV visibility all Cats, LNAV/VNAV visibility all Cats, LNAV Cats C/D visibility, and Circling Cat D visibility ¼ mile; increase Circling Cat C visibility ½ mile.

MISSED APPROACH:
Climb to 2100 direct WBSI and on track 076° to LAMKE and hold.

AWOS-3PT 118.725	CHARLESTON APP CON 120.7 306.925	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



2100	WBSI	tr 076°	LAMKE		
* LNAV only.					
RW35 1.3 NM to RW35					
LATNY 1700 351° 2400					
GP 3.00° TCH 40					
1.3 NM 3.6 NM 6.1 NM					
CATEGORY	A	B	C	D	
LPV DA	398-1 303 (300-1)				
LNAV/VNAV DA	447-1¼ 352 (400-1¼)				
LNAV MDA	560-1 465 (500-1)		560-1¾ 465 (500-1¾)		
CIRCLING	620-1 519 (600-1)	640-1 539 (600-1)	700-1½ 599 (600-1½)	700-2 599 (600-2)	

SE-2, 06 AUG 2026 to 03 SEP 2026

SE-2, 06 AUG 2026 to 03 SEP 2026