

WAAS CH 82232 W05A	APP CRS 049°	Rwy Ldg TDZE 96 Apt Elev 101
--	------------------------	--

RNAV (GPS) RWY 5

LOWCOUNTRY RGNL (RBW)

⚠


For uncompensated Baro-VNAV systems, procedure NA below -15°C (5°F) or above 54°C (130°F).
DME/DME RNP-0.3 NA. VDP and Baro-VNAV NA when using Charleston AFB/Intl altimeter setting.

⚠

Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Charleston AFB/Intl altimeter setting and increase all DA 78 feet and all MDA 80 feet; increase LPV, LNAV/VNAV all Cats and Circling Cat D visibility ¼ mile, increase LNAV Cat C - D visibility ½ mile, increase Circling Cat C visibility ½ mile.

MISSED APPROACH:
Climb to 2100 direct LAMKE and hold.

AWOS-3PT 118.725	CHARLESTON APP CON 120.7 306.925	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



ELEV 101 TDZE 96	
4 NM Holding Pattern 2400 ← 229° 049° → GP 3.00° TCH 53	
MUTCY VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 49). LIBME 1700 REFOK 2 NM to RW05 *1.1 NM to RW05 RW05 *760 *1.1 NM to RW05 RW05	
7 NM 2.9 NM 0.9 NM 1.1 NM	
CATEGORY	A B C D
LPV DA	431-1 335 (400-1)
LNAV/VNAV DA	507-1 411 (500-1)
LNAV MDA	540-1 444 (500-1) 540-1 444 (500-1)
CIRCLING	620-1 640-1 700-1 700-2 519 (600-1) 539 (600-1) 599 (600-1) 599 (600-2)