

LOC I-IER <u>110.5</u>	APP CRS 342°	Rwy Ldg TDZE Apt Elev	5003 121 121
----------------------------------	------------------------	-----------------------------	---

LOC RWY 35
NATCHITOCHES RGNL (IER)

T
A NA

Helicopter visibility reduction below $\frac{3}{4}$ SM NA. When local altimeter setting not received, use Alexandria Intl altimeter setting: increase all MDA 100 feet and S-35 Cat C visibility $\frac{1}{4}$ SM and Circling Cat C visibility $\frac{1}{2}$ SM. For inop ODALS when using Alexandria Intl altimeter setting, increase S-35 Cat C visibility $\frac{1}{8}$ mile. Inop table does not apply to S-35 Cat A/B. ADF required.

ODALS



MISSED APPROACH: Climb to 1000 then climbing left turn to 2000 direct OOC NDB and hold.

AWOS-3 119.025	MAKS APP CON 125.4 302.2	GCO 135.075	UNICOM 122.8 (CTAF) ①
--------------------------	------------------------------------	-----------------------	---------------------------------

ADF REQUIRED

LOCALIZER 110.5

 $\text{H}-\text{ER} \quad \begin{array}{c} \bullet \bullet \\ \bullet \bullet \\ \bullet \bullet \end{array}$

MSA OOC 25 NM

2600

MARTA
AEX 61.5

2000
106°
24.3)

IAF
NATCHITOCES
407 OOC 

319

162°
1 min
34'

1700
42° (7.1)

Procedure NA for arrivals
at AEX VORTAC
on V212 eastbound.

IAF
ALEXANDRIA
116.1 AEX
Chan 108

ELEV	121		TDZE	121
------	-----	--	------	-----

MIRL Rwy 7-25 and 17-35 **L**
REIL Rwy 7 and 17 **L**

FAF to MAP 4.2 NM

Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24

NATCHITOCHES, LOUISIANA

Amdt 4B 15JUL21

31°44'N-93°06'W

NATCHITOCHEs RGnL (IER)

LOC RWY 35

SC-4, 06 AUG 2026 to 03 SEP 2026

SC-4, 06 AUG 2026 to 03 SEP 2026