



WAAS CH 69639 W29A	APP CRS 290°	Rwy Ldg TDZE 413 Apt Elev 413
--	------------------------	---

RNAV (GPS) RWY 29

POTOMAC AIRPARK (W35)

RNP APCH.	Procedure NA at night. Rwy 29 helicopter visibility reduction below 1 SM NA. Obtain local altimeter setting on CTAF; when not received, use Martinsburg altimeter setting and increase all MDAs 80 feet and increase LNAV Cat A visibility ¼ SM.	MISSED APPROACH: Climb to 3500 direct ALLAH and hold.
-----------	--	--

POTOMAC APP CON 126.825 239.025	CTAF 122.9
---	----------------------



Visual Segment - Obstacles.				
3500 ALLAH				
FAMOX 3.1 NM to RW29				
DELIA 2600				
BAATI 3500				
RW29				
3.1 NM 2.6 NM 4.8 NM				
CATEGORY	A	B	C	D
LP MDA	1180-1 767 (800-1)	1180-1¼ 767 (800-1¼)	1180-2½	767 (800-2½)
LNAV MDA	1220-1 807 (900-1)	1220-1¼ 807 (900-1¼)	1220-2½	807 (900-2½)
CIRCLING	1240-1¼ 827 (900-1¼)	1280-1¼ 867 (900-1¼)	1700-3 1287 (1300-3)	1780-3 1367 (1400-3)