

WAAS
CH **63210**
W05A

APP CRS
050°

Rwy Idg **4351**
TDZE **74**
Apt Elev **74**

RNAV (GPS) RWY 5

BERKELEY COUNTY (MKS)

RNP APCH-GPS.


▼

▲ NA

Circling to Rwy 23 NA at night. Baro-VNAV NA when using Charleston AFB/Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15° C or above 54° C. Visibility reduction by helicopters NA. When local altimeter setting not received, use Charleston AFB/Intl altimeter setting: increase LPV DA to 451 feet; LNAV/VNAV DA to 513 feet; increase all MDA 60 feet and increase LNAV Cat C and Circling Cat C/D visibility ¼ SM. VDP NA when using Charleston AFB/Intl altimeter setting.

MISSED APPROACH: Climb to 2000 direct URICU and via 117° track to CUBBY and hold.

AWOS-3 119.175	CHARLESTON APP CON 121.275 379.925	UNICOM 123.05 (CTAF) 0
--------------------------	--	----------------------------------



4 NM Holding Pattern		ZAVIK	2000	URICU	CUBBY
			1600	117° TRK	
GP 3.00° TCH 46				* 1.3 NM to RWY 5	* LNAV only
					RWY 5
CATEGORY	A	B	C	D	
LPV DA	407-1¼		333 (400-1¼)		
LNAV/VNAV DA	469-1½		395 (400-1½)		
LNAV MDA	520-1	446 (500-1)	520-1¼	520-1½	
			446 (500-1¼)	446 (500-1½)	
CIRCLING	580-1	620-1	700-1¾	860-2½	
	506 (600-1)	546 (600-1)	626 (700-1¾)	786 (800-2½)	

