

WAAS CH 40218 W36A	APP CRS 360°	Rwy Ldg TDZE Apt Elev	5001 1003 1003
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 36

CENTRAL KENTUCKY RGNL (R.G.A)


⚠

⚠


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Lexington altimeter setting and increase LPV DA to 1331 feet, LNAV/VNAV DA to 1345 feet and all MDA 80 feet; increase LPV all Cats and LNAV/VNAV all Cats visibility ¼ mile; increase LNAV Cats C and D ⅝ mile and Circling visibility Cat D ¼ mile. Helicopter visibility reduction below ¾ SM NA. VDP and Baro-VNAV NA when using Lexington altimeter setting.


MISSED APPROACH: Climb to 3100 direct QEFFO and hold.

AWOS-3 119.625	LEXINGTON APP CON 120.15 259.3	UNICOM 122.725 (CTAF) 0
--------------------------	--	-----------------------------------



ELEV 1003	TDZE 1003
-----------	-----------



3100	QEFFO	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 26).		4 NM Holding Pattern
				
*LNAV only.				
CATEGORY				
LPV DA	1264-7/8		261 (300-7/8)	
LNAV/VNAV DA	1278-7/8		275 (300-7/8)	
LNAV MDA	1460-1 457 (500-1)		1460-13/8 457 (500-13/8)	
CIRCLING	1460-1 457 (500-1)	1520-1 517 (600-1)	1520-11/2 517 (600-11/2)	1780-21/2 777 (800-21/2)