

RADAR INSTRUMENT APPROACH MINIMUMS

NORFOLK NS (CHAMBERS FLD) (KNGU)

Norfolk, VA Amdt 1 22JAN26 (26106) (USN)

ELEV 15

RADAR - (E) 119.2x 120.2x 279.525 322.525 335.8 353.55 

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR ¹	10 ^{2 3} 28 ^{4 5}	3.0°/54/1020 3.0°/37/719	ABCDE ABCDE	114-¾ 319-¾	100 305	(100-¾) (400-¾)
PAR W/O GS ¹	28 ^{5 6 7} 10 ⁸		AB CDE AB CDE	440-⅞ 440-1 460-⅝ 460-⅞	426 426 446 446	(500-⅞) (500-1) (500-⅝) (500-⅞)
ASR	28 ^{5 9 10} 10 ¹¹		AB CDE AB CDE	440-¾ 440-1 720-½ 720-1⅞	426 426 706 706	(500-¾) (500-1) (800-½) (800-1⅞)
CIR PAR W/O GS ^{12 13}	10 28		A B C DE A B C DE	520-1 540-1 540-1½ 600-2 520-1⅞ 540-1⅞ 540-1½ 600-2	505 525 525 585 505 525 525 585	(600-1) (600-1) (600-1½) (600-2) (600-1⅞) (600-1⅞) (600-1½) (600-2)
CIR ASR ^{12 13}	28 10		A B C DE AB C D E	520-1 540-1 540-1½ 600-2 720-1 720-2 720-2¼ 720-2½	505 525 525 585 705 705 705 705	(600-1) (600-1) (600-1½) (600-2) (800-1) (800-2) (800-2¼) (800-2½)

06 AUG 2026 to 03 SEP 2026

06 AUG 2026 to 03 SEP 2026

¹No-NOTAM MP Mon 1030-1430Z++.

²When ALS inop, increase vis to ½ mile.

³PAPI RRP/TCH 669/35 not coincident with PAR RPI/TCH 1020/54.

⁴When ALS inop, increase vis to ⅞ mile.

⁵Helicopter vis reduction below ¾ mile not authorized.

⁶When ALS inop, increase CAT AB vis to 1⅞ mile, CAT CDE vis to 1¼ miles.

⁷Step down fix at 3 NM from RPI, 960 min.

⁸When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1¼ miles.

⁹When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1¼ miles.

¹⁰Step down fix at 3 NM from thld, 1000 min.

¹¹When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 2 miles.

¹²Cir not auth south of Rwy 10-28.

¹³Norfolk NS Heliport lctd 1 NM NW, use caution in cir aprch.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR INSTRUMENT APPROACH MINIMUMS

OCEANA NAS (APOLLO SOUCEK FLD) (KNTU)

Virginia Beach, VA Amdt 8 12JUN25 (25163) (USN)

ELEV 22

RADAR¹ - (E) 124.825 310.8 328.4 346.4 348.75 352.1 363.1 

	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u>	<u>CEIL-VIS</u>
PAR	5R ²	3.0°/50/947	ABCDE	119-¾	100	(100-¾)
	23L ²	3.0°/50/962	ABCDE	121-¾	100	(100-¾)
	32L ²	3.0°/50/952	ABCDE	122-¾	100	(100-¾)
	5L	3.0°/50/956	ABCDE	120-½	100	(100-½)
	23R	3.0°/50/959	ABCDE	120-½	100	(100-½)
	32R	3.0°/50/955	ABCDE	120-½	100	(100-½)
ASR ³	5R ⁴		AB	420-½	401	(400-½)
			CDE	420-¾	401	(400-¾)
	23L ⁴		AB	440-½	419	(500-½)
			CDE	440-¾	419	(500-¾)
	32L ⁴		AB	440-½	418	(500-½)
			CDE	440-¾	418	(500-¾)
	5L		AB	440-1	420	(500-1)
			CDE	440-1½	420	(500-1½)
	14L		AB	440-1	421	(500-1)
			CDE	440-1¼	421	(500-1¼)
	14R		AB	440-1	419	(500-1)
			CDE	440-1½	419	(500-1½)
	23R		AB	440-1	420	(500-1)
			CDE	440-1½	420	(500-1½)
SIDESTEP ⁵	5L		AB	440-1	420	(500-1)
			C	440-1½	420	(500-1½)
			DE	440-2	420	(500-2)
	23L		AB	440-1	419	(500-1)
			C	440-1½	419	(500-1½)
			DE	440-2	419	(500-2)
	23R		AB	440-1	420	(500-1)
			C	440-1½	420	(500-1½)
			DE	440-2	420	(500-2)
	32R		AB	440-1	420	(500-1)
			C	440-1½	420	(500-1½)
			DE	440-2	420	(500-2)
CIR	ALL RWY		AB	500-1	478	(500-1)
			C	600-1½	578	(600-1½)
			D	600-2	578	(600-2)
			E	900-3	878	(900-3)

¹No-NOTAM preventive maint 1100-1300Z++ Tue.
²When ALS inop, increase CAT ABCDE vis to ½ mile.
³Step Down Fix at 3 NM from thld, 1020' min.
⁴When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1½ miles.
⁵Sidestep ASR only.

06 AUG 2026 to 03 SEP 2026

06 AUG 2026 to 03 SEP 2026

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

26134

N3

RADAR INSTRUMENT APPROACH MINIMUMS

PATUXENT RIVER NAS (TRAPNELL FIELD) (KNHK)

Patuxent River, MD Amdt 3 07AUG25 (25219) (USN)

ELEV 39

RADAR - (E) 120.05 121.0 135.025 250.3 257.75 281.8 318.8 348.0 362.6



	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
PAR ¹	6 ²	3.0°/51/1086	ABCDE	139-¼	100	(100-¼)
	24	3.0°/50/949	ABCDE	120-½	100	(100-½)
	14 ³	3.0°/50/983	ABCDE	127-½	100	(100-½)
	32	3.0°/50/938	ABCDE	118-½	100	(100-½)
ASR	14 ^{3,4}		ABCDE	400-1	373	(400-1)
	32 ⁵		AB	440-1	422	(500-1)
			CDE	440-1¼	422	(500-1¼)
	6 ^{6,7}		AB	520-½	481	(500-½)
			CDE	520-1	481	(500-1)
	24 ⁵		AB	440-1	420	(500-1)
			CDE	440-1½	420	(500-1½)
CIR	6-24, 14-32		A	520-1	481	(500-1)
			B	560-1	521	(600-1)
			C	620-1½	581	(600-1½)
			D	700-2	661	(700-2)
			E	820-2¾	781	(800-2¾)

¹PAR No-NOTAM preventive maint period Wed 1300-1700Z++.
²When ALS inop, increase vis to ½ mile.
³CAUTION: High volume VFR traffic in vicinity of FAF during VMC.
⁴Step Down Fix at 2 NM from thld, 700' min.
⁵Step Down Fix at 3 NM from thld, 1020' min.
⁶Step Down Fix at 3 NM from thld, 1040' min.
⁷When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1½ miles.

QUANTICO MCAF (TURNER FLD) (KNYG)

Quantico, VA Amdt 9 27NOV25 (25331) (USN)

ELEV 10

RADAR¹ - 120.925 351.95 353.65 363.15



	<u>RWY</u>	<u>GP/TCH/RPI</u>	<u>CAT</u>	<u>DA/</u> <u>MDA-VIS</u>	<u>HAT/</u> <u>HATH/</u> <u>HAA</u>	<u>CEIL-VIS</u>
ASR ^{2,3}	2		AB	560-1	551	(600-1)
			CDE	560-1½	551	(600-1½)
CIR ASR ⁴	2		A	560-1	550	(600-1)
			B	660-1	650	(700-1)
			C	700-2	690	(700-2)
			D	740-2¼	730	(800-2¼)
			E	760-2¾	750	(800-2¾)

¹GCA avbl daily during published field opr hours. Ctc twr for freq asgn.
²VGSI and final descent angle not coincident.
³Step Down Fix 3 NM from thld, 1000 min.
⁴Circling NA W of Rwy 2-20.

RADAR INSTRUMENT APPROACH MINIMUMS

RADAR MINS

26134

N3

NE-3

06 AUG 2026 to 03 SEP 2026

06 AUG 2026 to 03 SEP 2026