

ILS or LOC X RWY 16

LOC I-MUK 108.9	APCH CRS 158°	Rwy Idg 12,134 TDZE 4083 Arpt Elev 4093	[USAF]
---------------------------	-------------------------	--	--------

HOLLOMAN AFB (KHMN)

RADAR or DME required.
 * When ALS inop, increase vis to ¾ mile.

ATIS ★ 273.5	ALBUQUERQUE CENTER 132.65 257.6	APP CON 120.6 269.225	TOWER ★ 119.3 254.4	GND CON 127.05 275.8
-------------------------------	--	--	--------------------------------------	---------------------------------------

**** When ALS inop, increase CAT AB vis to 1 mile; CAT CDE vis to 1½ miles.**
When circling Rwy 25 at Night, operations VGSI required, remain on or above VGSI glidepath until threshold.
CAUTION: When Rwy 22 VGSI inop, circling to Rwy 22 NA at night.
USAF Only: When Rwy 16 VGSI inop, straight-in Rwy 16 authorized at night with aircrew command approval.
INBOUND WEST: Airspace West Restricted. Expect routing via CORONA.

Unlit terrain 0' AGL/4082' MSL, 136' right of course.
CAUTION: ILS TCH 41'. Height group 4 (B-747/767/777, L-1011, DC-10, A-300, B-1, KC-10, E-4, C-5, and VC-25) wheel crossing height 16'.

EMERG SAFE ALT 100 NM 14,200 VGSI and ILS glidepath not coincident (VGSI angle 3.00/TCH 50).	5000 crs 158° 7000 HMN R-320 JOBAM HMN 12
--	--

CATEGORY	A	B	C	D	E
S-ILS 16*	4283-½		200	(200-½)	
S-LOC 16**	4600-½	517 (600-½)	4600-1	517	(600-1)
CIRCLING	4620-1	527 (600-1)	5200-3	1107 (1200-3)	5300-3 (1207 (1300-3))

HIRL all rwys
REIL Rwy 22