

WAAS CH 82317 W25A	APP CRS 245°	Rwy Ldg 11801 TDZE 624 Apt Elev 633
--	------------------------	--

RNAV (GPS) RWY 25

OSCODA/WURTSMITH (OSC)


RNP APCH.

▼ Circling RNA southeast of Rwy 7-25. Baro-VNAV and VDP NA when using Alpena altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Alpena altimeter setting and increase all DA 96 feet and all MDA 100 feet. Increase LNAV/VNAV all Cats and LNAV and Circling Cat C visibility ¼ SM, and Circling Cat D visibility ½ SM. For inop ALS, increase LNAV Cats C and D visibility to 1 SM. For inop ALS when using Alpena altimeter setting, increase LPV all Cats visibility to ¾ SM.

MALSR

MISSED APPROACH:
Climb to 3000 direct
CEDPA and hold.

AWOS-3P 118.7	MINNEAPOLIS CENTER 125.475 269.45	UNICOM 123.0 (CTAF) 0
-------------------------	---	---------------------------------



3000	CEDPA	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).	4 NM Holding Pattern
*LNAV only.			
RW25	SALTR	KOWKU	
0.9 NM	2500	2500	2500
0.9 NM	4.7 NM	6.1 NM	
CATEGORY	A	B	C
LPV DA	824-½	200 (200-½)	
LNAV/VNAV DA	1004-¾	380 (400-¾)	
LNAV MDA	980-½ 356 (400-½)	980-⅝ 356 (400-⅝)	980-1 356 (400-1)
CIRCLING	1140-1 507 (600-1)	1160-1½ 527 (600-1½)	1300-2 667 (700-2)

