


VORTAC IWA 113.3 Chan 80	APP CRS 302°	Rwy Ldg	30C	30R
		TDZE	10201	9301
			1380	1382
		Apt Elev	1384	1384

VOR or TACAN RWY 30C
MESA GATEWAY (IWA)

⚠ When local altimeter setting not received, use Phoenix Sky Harbor Intl altimeter setting and increase all MDA 80 feet, increase S-30C, SIDESTEP 30R, and Circling Cats C/D/E visibility ¼ SM.

MISSED APPROACH: Climb to 2800 then climbing right turn to 5000 via heading 145° and IWA VORTAC R-015 to IWA VORTAC and hold, continue climb-in-hold to 5000 (TACAN aircraft continue via IWA VORTAC R-122 to HALLB INT/IWA 9.9 DME and hold, continue climb-in-hold to 5000, hold SE, LT, 302° inbound).

ATIS 133.5 270.275	PHOENIX APP CON 124.9 353.8	GATEWAY TOWER* 120.6 (CTAF) 289.4	GND CON 128.25 275.8
------------------------------	---------------------------------------	---	--------------------------------



2800 5000 IWA IWA SNOWL INT IWA 6.4

↑ hdg 145°

IWA VORTAC IWA 0.6

ALBANY IWA 1.7 IWA 2.5

≤ 3.03° TCH 49

1.2 NM 0.7 3.9 NM

1940*

3300

122°

302°

3700

Remain within 10 NM

* 2020 when using Phoenix Sky Harbor Intl altimeter setting.

CATEGORY	A	B	C	D	E
S-30C	1940-1 560 (600-1)		1940-1½ 560 (600-1½)	1940-1¾ 560 (600-1¾)	1940-2 560 (600-2)
SIDESTEP 30R	1940-1 558 (600-1)		1940-1½ 558 (600-1½)	1940-2 558 (600-2)	
CIRCLING	1940-1 556 (600-1)		1940-1½ 556 (600-1½)	2000-2 616 (700-2)	2020-2¼ 636 (700-2¼)
DME MINIMUMS					
S-30C	1800-1 420 (500-1)		1800-1¼ 420 (500-1¼)		1800-1½ 420 (500-1½)
SIDESTEP 30R	1800-1 418 (500-1)		1800-1½ 418 (500-1½)	1800-2 418 (500-2)	
CIRCLING	1880-1 496 (500-1)		1880-1½ 496 (500-1½)	2000-2 616 (700-2)	2020-2¼ 636 (700-2¼)

TFD R-081

(IAF) GIZZA INT TUS 46

R-336 9000 336° (46)

TUCSON 116.0 TUS 107 Chan 107

ELEV 1384

TDZE 30C 1380 TDZE 30R 1382

HIRL Rwy 12L-30R and 12C-30C REIL Rwy 12L and 30R MIRL Rwy 12R-30L

FAF to MAP 5.8 NM

Knots 60 90 120 150 180 Min:Sec 5:48 3:52 2:54 2:19 1:56

SW-4, 03 SEP 2026 to 01 OCT 2026

SW-4, 03 SEP 2026 to 01 OCT 2026