

WAAS CH 82241 W04D	APP CRS 036°	Rwy Ldg 10000 TDZE 645 Apt Elev 645
--	------------------------	--

RNAV (GPS) Z RWY 4L
DETROIT METRO WAYNE COUNTY (DTW)

RNP APCH.


Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000.

ALSF-2



MISSED APPROACH: Climb to 1100 then climbing left turn to 4000 direct DOHNT and hold.

D-ATIS 133.675	DETROIT APP CON 124.05 284.0	METRO TOWER 135.0 317.725	GND CON 121.8 (NW) 119.45 (NE) 132.725 (SW) 119.25 (SE)
--------------------------	--	-------------------------------------	---



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).				
ASLI NATIY REGGE PAYED HIPKA 3000 3000 3000 2000 1.8 NM to RW04L GP 3.00° TCH 55 3000 3000 2000 *1260 *1 NM to RW04L 4.2 NM 3.1 NM 3.1 NM 2.3 NM 0.8 NM 1 NM				
CATEGORY	A	B	C	D
LPV DA	845/18		200 (200-½)	
LNAV/VNAV DA	1046/40		401 (500-¾)	
LNAV MDA	1040/24	395 (400-½)		1040/35 395 (400-⅝)
CIRCLING	1180-1	535 (600-1)		1180-1½ 535 (600-1½) 1240-2 595 (600-2)

TDZL/RCLS Rwy 3R, 4L, 4R and 22R
REIL Rwy 3L, 9L, 9R and 21R
HIRL all Rwy