

WAAS CH 82308 W21A	APP CRS 207°	Rwy Ldg TDZE 1276 Apt Elev 1276
--	------------------------	---

RNAV (GPS) RWY 21

EPHRATA MUNI (EPH)

RNP APCH.


▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 46°C. VDP and Baro-VNAV NA when using Moses Lake/Grant County Intl altimeter setting. When local altimeter setting not received, use Moses Lake/Grant County Intl altimeter setting and increase all DA/MDA 40 feet; increase visibility LPV all Cats, and LNAV Cats C and D ¼ SM.

MISSED APPROACH: Climb to 4500 direct UDECU and hold.

ASOS 135.775	GRANT COUNTY APP CON * 126.4 379.95	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



4500 ↑	UDECU △	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 40).		TICYU	4 NM Holding Pattern
*LNAV only	*2.2 NM to RW21	CIGUM	207°	207°	3800
RW21			2900		GP 3.00° TCH 51
2.2 NM	2.7 NM	6.1 NM			
CATEGORY	A	B	C	D	
LPV DA	1526-¾ 250 (300-¾)				
LNAV/ VNAV DA	2171-4 895 (900-4)				
LNAV MDA	2020-1 744 (800-1)	2020-1¼ 744 (800-1¼)	2020-2¼ 744 (800-2¼)	2020-2½ 744 (800-2½)	

