

RNAV (RNP) Y RWY 27
HELENA RGNL (HLN)

T For uncompensated Baro-VNAV systems,
❄ -16°C procedure NA below -28°C or above 54°C.
 Missed approach requires RNP less than 1.0.
 For inop ALS, increase RNP 0.30 DA* visibility
 all Cnts to 1% SM.



*Missed approach requires minimum climb of 260 feet per NM to 7900; if unable to meet climb gradient, see RNAV (RNP) Z RWY 27.

Procedure NA for arrivals at HLN VORTAC on V113 northeast bound.

Procedure NA for arrivals at SUZZY on V343 westbound.

Procedure NA for arrival on HIA VOR/DME arrival radials 353 CW 078.

MSA RW27 25 NM

ELEV 3877 TDZE 3852

REIL Rwy 9, 17, and 35
MIRL Rwy 5-23 and 17-35
HIRL Rwy 9-27

12000
↑
ZKSA
tr 271°
See planview for multiple IF locations.

tr 271°
MUSEW
tr 271°
KISTY
tr 265°
KELTY
tr 275°
PIXXI
△
△
GOKME

1.2% UP
AS44 X 75
0.3% DOWN
9000 X 150
Rwy 10-28
1584 X 75
TWR
AG
271°

JEXUT
6500
271°
7000
GP 3.00°
TCH 55

CATEGORY	A	B	C	D
RNP 0.15 DA*	4284-¾		432 (500-¾)	
RNP 0.30 DA*	4321-1		469 (500-1)	

AUTHORIZATION REQUIRED

RNAV (RNP) Y RWY 27

NW-1, 03 SEP 2026 to 01 OCT 2026