


WAAS CH 62802 W32A	APP CRS 320°	Rwy Ldg 7278 TDZE 793 Apt Elev 796
--	------------------------	---


RNAV (GPS) Y RWY 32

INDIANAPOLIS INTL (IND)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. **RVR 1800 authorized with use of FD or AP or HUD to DA.			MALSR	MISSED APPROACH: Climb to 3000 direct KEADY and hold.	
D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC



ELEV 796	D	TDZE 793
-----------------	----------	-----------------



3000 ↑		KEADY ✦		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).		OZMOE 4500	
*LNAV only		*1 NM to RW32		BTTLR 2400		320°	
RW32 1 NM		3.9 NM		2400		GP 3.00° TCH 53	
CATEGORY		A		B		C	
LPV DA		** 993/24		200 (200-½)			
LNAV/ VNAV DA		1069/24		276 (300-½)			
LNAV MDA		1160/24 367 (400-½)		1160/35 367 (400-¾)			
CIRCLING		1420-1 624 (700-1)		1420-1¾ 624 (700-1¾)		1560-2½ 764 (800-2½)	