KEY WEST, FLORIDA

RNAV (GPS) RWY 4

APCH CRS	Rwy ldg	7001
037°	TDZE	4
	Arpt Elev	6

(USN) KEY WEST NAS (BOCA CHICA FLD) (KNQX)

RNP APCH-GPS

MISSED APPROACH: (Do not exceed 230 KIAS until CEGEX.) Climb to 1600 direct CEGEX, track 314° to FISLI, track 229° to SKIPP and hold.

ATIS★	APP CON★	NAVY KEY WEST TOWER★	GND CON	ASR/PAR
307.025	124.025 313.7	118.575 340.25	121.7 336.45	

CONTIGUOUS US ADIZ

FISLI

CAUTION: Balloon with strobe light on unmarked cable to 14,000 in R-2916.

R2916

229° (10.4)

314° (9)

CEGEX

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (129°F).

SKIPP

101°

230K

281°

4 NM

HOLD 4000 1600

KEY WEST EYW

1600

183° (9.6)

406

KEY WEST INTL

196

105

RW04

BIPIN

1600

248° (26.4)

037°

(FAF) MEDAC

1600

038° (5)

MSA RW04 25 NM

15,000

4 NM

238°

230K

058°

(IF/IAF) TAVDE

HOLD 4000 1600

CONTIGUOUS US ADIZ

EMERG SAFE ALT 100 NM 15,000

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 35).

1600 CEGEX

ELEV 6

TDZE 4

4 NM Holding Pattern

4000 1600

238°

058°

TAVDE

038°

MEDAC

037°

1.3 NM to RW04

RW04

1600

GP 3.00°

TCH 45

4.9 NM

CATEGORY	A	B	C	D
LNAV/VNAV DA	254-¾ 250	(300-¾)	255-¾ 251 (300-¾)	266-⅞ 262 (300-⅞)
LNAV MDA	460-1 456	(500-1)	460-1⅜ 456	(500-1⅜)
CIRCLING	460-1 454 (500-1)	500-1 494 (500-1)	500-1½ 494 (500-1½)	580-2 574 (600-2)

10,001 x 200

7000 x 150

7001 x 150

TWR

BCN

154

037°

HIRL all rwys

SE-3, 03 SEP 2026 to 01 OCT 2026

SE-3, 03 SEP 2026 to 01 OCT 2026