ASOS 119.925
CLNC DEL
121.8 257.65
132.075 269.075 (When Tower Closed)
GND CON
121.8 257.65
MARTINSBURG TOWER ★
124.3 (CTAF) 233.7
POTOMAC DEP CON
126.825 239.025

TOP ALTITUDE: 3000

N

P-56B

P-56A

TAKEOFF MINIMUMS
Rwy 8: Standard.
Rwy 26: Standard with a minimum climb of 225' per NM to 2100.

NOTE: RNAV 1.
NOTE: RADAR required.
NOTE: DME/DME/IRU or GPS required.
NOTE: Turbo-jets only.
NOTE: Takeoff Rwy 8, if issued an ATC heading that requires a westbound turn, climb heading 081° to 1200 prior to turning for obstacle avoidance.
NOTE: Takeoff Rwy 26, if issued an ATC heading that requires a right turn, climb heading 261° to 2400 prior to turning for obstacle avoidance.

POOCH
3000

240°
(8)

SCRAM

9800
241°
(28)

DANOO

16400
242°
(33)

WALCE

18000
228°
(21)

GLANC

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

Climb on heading assigned by ATC, expect RADAR vectors to POOCH, then on track 240° to SCRAM, thence. . . .

. . . . as depicted. Maintain 3000, expect clearance to filed altitude within ten (10) minutes after departure.

GLANC TRANSITION (SCRAM6.GLANC):

SCRAM SIX DEPARTURE (RNAV)
(SCRAM6.SCRAM) 31DEC20
MARTINSBURG, WEST VIRGINIA
EASTERN WV RGNL/SHEPHERD FLD (MRB)
NE-4, 03 SEP 2026 to 01 OCT 2026