

MAYNR THREE DEPARTURE (RNAV)

MIAMI, FLORIDA

**TOP ALTITUDE:
ASSIGNED BY ATC**

RNAV 1 - DME/DME/IRU or GPS.
From SLIPT to MAXIM: RNAV 1- GPS.
From SLIPT to CANOA: RNAV 1- GPS.

ADAR required for non-GPS equipped aircraft.
ADAR required.

MIAMI DEP CON
126.85 290.325
ATIS
125.9
CLINC DEL
119.2
GND CON
120.025
COPIA LOCKA TOW
134.675 (CTAF)

TAKEOFF MINIMUMS

Rwy 9L: Standard with minimum climb of 500'/NM to 1000.

Rwy 9R: Standard with minimum climb of 500'/NM to 700.

Rwys 12, 27R: Standard with minimum climb of 500'/NM to 600.

Rwys 27L, 30: Standard with minimum climb of 500'/NM to 520.

NOTE: Jet aircraft only.

NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SE-3, 03 SEP 2026 to 01 OCT 2026

MIAMI, FLORIDA

MIAMI-OPA LOCKA EXEC (OPF)

MAYNR THREE DEPARTURE (RNAV)

(MAYNR3.MAYNR) 31OCT24