RNAV (GPS) RWY 34L

MIDLAND INTL AIR AND SPACE PORT (MAF)

WAAS	APP CRS	Rwy Ldg	9501
CH 66029	346°	TDZE	2858
W34A		Apt Elev	2872

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 26°C (78°F). Circling Rwy 16L NA at night. DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 5100 direct PERAE and hold.

ATIS	MIDLAND APP CON ★	MIDLAND TOWER ★	GND CON	UNICOM
126.8 235.975	124.6 290.4	118.7 (CTAF) 273.45	121.9 348.6	122.95



ELEV 2872 D TDZE 2858





CATEGORY	A	B	C	D
LPV DA	3058- ¾ 200 (200- ¾)			
LNAV/VNAV DA	3203- 1⅛ 345 (400- 1⅛)			
LNAV MDA	3280-1 422 (500-1)		3280-1¼ 422 (500- 1¼)	
CIRCLING	3440-1 568 (600-1)		3440-1½ 568 (600-1½)	3520-2 648 (700-2)

SC-3, 03 SEP 2026 to 01 OCT 2026
SC-3, 03 SEP 2026 to 01 OCT 2026