RNAV (GPS) RWY 4

MIDLAND INTL AIR AND SPACE PORT (MAF)

WAAS	APP CRS	Rwy Ldg	4605
CH 90529	045°	TDZE	2851
W04A		Apt Elev	2872

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 25°C (77°F). Circling Rwy 16L NA at night. Rwy 4 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 4700 direct AYUPA and hold.

ATIS	MIDLAND APP CON★	MIDLAND TOWER★	GND CON	UNICOM
126.8 235.975	124.6 290.4	118.7 (CTAF) L 273.45	121.9 348.6	122.95





CATEGORY	A	B	C	D
LPV DA	3051-¾ 200 (200-¾)			
LNAV/VNAV DA	3283-1½ 432 (500-1½)			
LNAV MDA	3360-1 509 (500-1)		3360-1⅜ 509 (500-1⅜)	
CIRCLING	3440-1 568 (600-1)		3440-1½ 568 (600-1½)	3520-2 648 (700-2)

ELEV 2872 D TDZE 2851



REIL Rwy 34L
MIRL Rwys 4-22 and 16L-34R L
HIRL Rwys 10-28 and 16R-34L

SC-3, 03 SEP 2026 to 01 OCT 2026
SC-3, 03 SEP 2026 to 01 OCT 2026