

LOC I-MLU <u>109.5</u>	APP CRS 042°	Rwy Ldg 7504 TDZE 78 Apt Elev 79
----------------------------------	------------------------	---

ILS or LOC RWY 4
MONROE RGNL (MLU)

ADF or DME required for procedure entry.

T Circling Rwy 14 NA at night. For inop ALS, increase S-LOC 4 Cat C/D visibility to 1 $\frac{3}{8}$ SM.

⚠ UXGOY FIX MINIMUMS: For inop ALS, increase S-LOC 4 Cat C/D visibility to RVR 5500.
ASR **RVR 1800 authorized with the use of FD or AP or HUD to DA.

ASR **RVR 1800 authorized with the use of FD or AP or HUD to DA.

DME from MLU VORTAC.

MALSR



MISSED APPROACH: Climb to 1800 then climbing right turn to 3000 direct MLU VORTAC and hold.

ATIS 125.05	MONROE APP CON ★ 118.15 290.475	MONROE TOWER ★ 118.9 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
----------------	------------------------------------	--	------------------	------------------

ALTERNATE MISSED
APCH FIX

SABAR

MLU 5.1

ML $\frac{1}{2}$

392

MONROE

117.2 MIU $\frac{1}{100}$

Chan 119

MSA MLCOM 25 NM

2200

250°

32

3100

LOCALIZER 109.5

LMU

CATEGORY	A	B	C	D
S-ILS 4		**278/24	200 (200-½)	
S-LOC 4	540/24	462 (500-½)	540/50	462 (500-1)
CIRCLING	580-1	501 (600-1)	740-1¾ 661(700-1¾)	1160-3 1081 (1100-3)
# UXGOY FIX MINIMUMS				
S-LOC 4	420/24	342 (400-½)	420/30	342 (400-¾)
CIRCLING	580-1	501 (600-1)	740-1¾ 661 (700-1¾)	1160-3 1081 (1100-3)

ELEV 79 **D** TDZE 78

042°

TWR

7504 X 150

8301 X 150

REIL Rwy 14 and 32

MRL Rwy 14-32

FAF to MAP 4.2 NM

Knots	60	90	120	150	180
Min:Sec	4:12	2:48	2:06	1:41	1:24