

WAAS
CH **56435**
W18A

APP CRS
184°

Rwy Ldg **4000**
TDZE **547**
Apt Elev **551**

RNAV (GPS) RWY 18


NORTHWEST ALABAMA RGNL (MSL)


RNP APCH.

Baro-VNAV NA when using Decatur altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). Rwy 18 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Decatur altimeter setting and increase LPV DA to 880, LNAV/VNAV DA to 1065 and all MDA 100 feet, increase LNAV Cat C visibility ¼ SM, increase Circling Cat C visibility ½ SM.

MISSED APPROACH:
Climb to 3000 direct PAMGE and hold.

ASOS 119.425	MEMPHIS CENTER 120.8 307.0	GCO 121.725	UNICOM 123.05 (CTAF)
------------------------	--------------------------------------	-----------------------	--------------------------------



ELEV 551	TDZE 547	3000 PAMGE VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 35). *LNAV only. VEGUY 2.2 NM to RW18 SOSBE 2300 4 NM Holding Pattern GP 3.15° TCH 57			
		81 12 6694 X 150 4000 X 100 36 AS 30			
CATEGORY		A	B	C	D
LPV DA		797-1	250 (300-1)		NA
LNAV/VNAV DA		982-1 3/8	435 (500-1 3/8)		NA
LNAV MDA		960-1	413 (500-1)	960-1 1/4 413 (500-1 1/4)	NA
CIRCLING		1040-1	489 (500-1)	1280-2 729 (800-2)	NA