ILS or LOC RWY 1

SAVANNAH/HILTON HEAD INTL (SAV)

LOC I-TPV	APP CRS	Rwy Ldg	7002
111.9	006°	TDZE	39
		Apt Elev	50

DME or RADAR required for procedure entry.

Autopilot coupled approach NA below 600.

MISSED APPROACH: Climb to 1000 then climb to 4000 on SAV VORTAC R-001 to TILLS INT/SAV 20 DME and hold.

ATIS	SAVANNAH APP CON★	SAVANNAH TOWER★	GND CON	UNICOM
123.75	125.3 371.875	125.975 (CTAF) L 257.8	121.9 348.6	122.95



ELEV 50 | D | TDZE 39



TDZL/RCLS Rwy 10
REIL Rwys 19 and 28 L
HIRL Rwys 1-19 and 10-28 L

FAF to MAP 5.9 NM

Knots	60	90	120	150	180
Min:Sec	5:54	3:56	2:57	2:22	1:58



CATEGORY	A	B	C	D
S-ILS 1	239/40 200 (200-¾)			
S-LOC 1	480/55 441 (500-1)		480-1⅜ 441 (500-1⅜)	
CIRCLING	520-1 470 (500-1)		740-2 690 (700-2)	740-2¼ 690 (700-2¼)

SE-4, 03 SEP 2026 to 01 OCT 2026
SE-4, 03 SEP 2026 to 01 OCT 2026