

WAAS CH 70419 W22A	APP CRS 222°	Rwy Ldg TDZE 4310 Apt Elev 4314
--	------------------------	---

RNAV (GPS) RWY 22

DEMING MUNI (DMN)

RNP APCH - GPS.


▼

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -23°C or above 40°C. Baro-VNAV NA when using Las Cruces altimeter setting. When local altimeter setting not received, use Las Cruces altimeter setting and increase all DA 114 feet and all MDA 120 feet; increase LPV and LNAV/VNAV all Cats visibility ¼ mile, increase LNAV Cats C and D visibility ¼ mile, increase Circling Cat B visibility ¼ mile and Circling Cats C and D visibility ½ mile. Rwy 22 helicopter visibility reduction below 1 SM NA. Straight-in Rwy 22 NA at night, Circling Rwy 22, 26 NA at night.

MISSED APPROACH:
Climb to 9000 direct GINEC and on track 274° to FAAST and hold.

ASOS 118.525	ALBUQUERQUE CENTER 128.2 285.5	UNICOM 122.8 (CTAF) 0
------------------------	--	---------------------------------



R-5115		ELEV 4314		TDZE 4310	
9000	GINEC	tr 274°	FAAST	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 44).	
ODLUE		JUTEF		7100	
RWY 22		ZIPKI 3.3 NM to RWY 22		Procedure Turn NA	
5400		6100		GP 3.00°	
3.3 NM		2.1 NM		TCH 52	
CATEGORY		A		B	
LPV DA		4560-1		250 (300-1)	
LNAV/VNAV DA		4637-1¼		327 (400-1¼)	
LNAV MDA		4660-1		350 (400-1)	
CIRCLING		4820-1		5020-2	
506 (600-1)		626 (700-1)		706 (800-2)	
				5020-2¼	
				706 (800-2¼)	
				MIRL Rwy 4-22	
				MIRL Rwy 8-26 0	