

ILS Z or LOC RWY 18R

LOC I-ALT 111.3	APCH CRS 175°	Rwy Idg 13,440 TDZE 1378 Arprt Elev 1382	[USAF]	ALTUS AFB (KLTS)
---------------------------	-------------------------	---	--------	------------------

DME or RADAR required.

▼ * When ALS inop, increase RVR to 55 and vis to 1 mile.
 ** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile;
 CAT CDE vis to 1½ miles.

ATIS ★ 109.8 273.5	FORT WORTH CENTER 133.5 350.35	APP CON 125.1 353.7	TOWER ★ 119.65 254.4	GND CON 121.85 275.8
------------------------------	--	-------------------------------	--------------------------------	--------------------------------

***Circling NA W of Rwy 18R-36L.

ATC Radar required for holding above 4000

CAUTION: Autopilot coupled operations NA below 1740 MSL.

LOCALIZER 111.3
 I-ALT

ALTUS
 109.8 LTS
 Chan 35

EMERG SAFE ALT 100 NM 4900

4000	OKKIE LTS 12	WATGAS RADAR	HOGIS RADAR	MRTHA RADAR	LTS 17
LTS R-176					

ELEV 1382	TDZE 1378

CATEGORY	A	B	C	D	E
S-ILS 18R	1578/40				
S-LOC 18R *	1760/40	382 (400-¾)	1760/45	382 (400-¾)	2300-3
CIRCLING ***	1780-1 398 (400-1)	1840-1 458 (500-1)	1880-1½ 498 (500-1½)	2080-2¼ 698 (700-2¼)	2300-3 918 (1000-3)
LOCAL ALTIMETER, WITHOUT LAST STEPDOWN FIX					
S-LOC 18R **	2040/40	662 (700-¾)	2040-1¾	662 (700-1¾)	
CIRCLING ***	2040-1	658 (700-1)	2040-1¾ 658 (700-1¾)	2080-2¼ 698 (700-2¼)	2300-3 918 (1000-3)

HIRL all Rwy's

SC-1, 03 SEP 2026 to 01 OCT 2026

SC-1, 03 SEP 2026 to 01 OCT 2026