

WAAS
CH **70622**
W14A

APP CRS
143°

Rwy Idg
TDZE
Apt Elev
5054
712
716

RNAV (GPS) RWY 14

SAULT STE MARIE MUNI/SANDERSON FLD (A.NJ)


RNP APCH.
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.
▲ Rwy 14 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Chippewa County Intl altimeter setting and increase all DA 45 feet and all MDA 60 feet. Increase LNAV/VNAV all Cats visibilities to 1¼ mile and LNAV Cat C visibility to 1½ mile.

MISSED APPROACH:
Climb to 3000 direct YIRUC and on track 147° to ALVUS and hold.

ASOS
118.375

TORONTO CENTER
132.65 344.5

UNICOM
122.7 (CTAF) 0



4 NM Holding Pattern KUCEB

2800 ← 323°
143° →

GP 3.00°
TCH 46

3000 YIRUC tr 147° ALVUS

CAKTA 2600 *1720

AJAPY 3.1 NM to RW14

RW14

*LNAV only

7 NM 2.7 NM 3.1 NM

CATEGORY A B C D

LPV DA 962-1 250 (300-1) NA

LNAV/VNAV DA 1137-1¾ 425 (500-1¾) NA

LNAV MDA 1240-1 528 (600-1) 1240-1¾ 528 (600-1¾) NA

MIRL Rwy 14-32 0

REIL Rws 14 and 32 0