

WAAS CH 99429 W36B	APP CRS 355°	Rwy Ldg TDZE 480 Apt Elev 542
--	------------------------	---

RNAV (GPS) Y RWY 36R

AUSTIN-BERGSTROM INTL (AUS)



RNP APCH-GPS.


▼ Use of FD or AP required during simultaneous operations. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. For inop ALS increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to 1½ SM and LNAV Cat C/D/E visibility to 1½ SM.

MALSR

MISSED APPROACH: Climb to 1000 then climbing right turn to 3000 direct HOOKK and hold.

D-ATIS 124.4	AUSTIN APP CON 127.225 317.65 (E) 120.875 270.25 (S) 119.0 370.85 (W)	AUSTIN TOWER 121.0 281.5	GND CON 121.9 348.6
------------------------	---	------------------------------------	-------------------------------



1000	3000	HOOKK	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 59).			
			BALLD			
						
CATEGORY	A	B	C	D	E	
LPV DA	680/18 200 (200-½)					
LNAV/ VNAV DA	970/50 490 (500-1)					
LNAV MDA	1000/24	520 (500-½)	1000/55 520 (500-1)			
CIRCLING	1040-1 498 (500-1)	1120-1 578 (600-1)	1200-1¾ 658 (700-1¾)	1200-2 658 (700-2)	NA	

SC-3, 03 SEP 2026 to 01 OCT 2026

SC-3, 03 SEP 2026 to 01 OCT 2026