

WAAS CH 57907 W21A	APP CRS 214°	Rwy Ldg TDZE Apt Elev	6500 522 547
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 21

BOWLING GREEN-WARREN COUNTY RGNL (BWG)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C. Baro-VNAV and VDP NA when using GLW altimeter setting. Circling Rwy 30 NA at night.
Rwy 21 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use GLW altimeter setting and increase LPV DA to 884 feet and all visibilities ½ SM. Increase LNAV/VNAV DA to 1150 feet and all visibilities ½ SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM.

MISSED APPROACH: Climb to 3100 direct WEDVO and hold.

ASOS
127.825

MEMPHIS CENTER
133.85 285.5

UNICOM
123.0 (CTAF) 0

ELEV **547** **D** TDZE **522**

3100 WEDVO

WISLI 2.1 NM to RW21

1.4 NM to RW21

1.4 NM 0.7 NM 3.6 NM 6 NM

UGATE 4 NM Holding Pattern

ZEZTA 2400

6000 3100

GP 3.00° TCH 55°

CATEGORY	A	B	C	D
LPV DA	807-¾ 285 (300-¾)			
LNAV/VNAV DA	1073-1½ 551 (600-1½)			
LNAV MDA	1020-1 498 (500-1)	1020-1¾ 498 (500-1¾)		
CIRCLING	1020-1 473 (500-1)	1120-1 573 (600-1)	1160-1¾ 613 (700-1¾)	1200-2 653 (700-2)

REIL Rwy 3 and 21 0

MIRL Rwy 12-30

HIRL Rwy 3-21 0

BOWLING GREEN, KENTUCKY

Amdt 1B 12JUN25

BOWLING GREEN-WARREN COUNTY RGNL (BWG)

36°58'N-86°25'W

RNAV (GPS) RWY 21