

WAAS CH 82109 W05A	APP CRS 049°	Rwy Ldg 9020 TDZE 573 Apt Elev 589
--	------------------------	---

RNAV (GPS) RWY 5

TERRE HAUTE RGNL (HUF')

RNP APCH.

▼

ASR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. VDP and Baro-VNAV NA when using Paris altimeter setting. When local altimeter setting not received, use Paris altimeter setting and increase all DA 61 feet, and all MDA 80 feet. Increase LPV all Cats visibility ¼ SM and Circling Cat C/D visibility ¼ SM. For inoperative ALS, increase LPV all Cats visibility to RVR 4500, LNAV/VNAV all Cats visibility to RVR 5500 and LNAV Cat C/D visibility to RVR 6000, when using Paris altimeter setting, increase LPV and LNAV/VNAV visibility all Cats to RVR 6000, increase LNAV Cat C/D visibility to 1 ¾ SM.

MALS

AS

MISSED APPROACH:
Climb to 2400 direct
IPEDY and hold.

ATIS 127.5 269.375	HULMAN APP CON 125.45 339.8	HULMAN TOWER 134.725 322.475	GND CON 121.6 348.6
------------------------------	---------------------------------------	--	-------------------------------

TERRE HAUTE TTH
2600 to POKHY
230° (15.1)

Procedure NA for arrival on TTH VORTAC
airway radials 140 CW 320.

MSA RW05 2.5 NM
2600

2600 NoPT
134° (8.4)

(IAF) IFIGO

(FAF) SOXME

(IF/IAF) POKHY

HOLD 6000
2600

4 NM

2100 049° (6)

2600 NoPT
316° (10.9)

1553

(IAF) GOZUM

RW05

VARUY
1.7 NM to
RW05

4 NM
Holding Pattern

POKHY

SOXME

VARUY
1.7 NM to
RW05

2400

IPEDY

GP 3.00°
TCH 40

6000
2600

229°

049°

049°

2100

*1140

*1 NM to
RW05

RW05

*LNAV only.

CATEGORY	A	B	C	D
LPV DA		875/24	302 (300-½)	
LNAV/ VNAV DA		924/40	351 (400-¾)	
LNAV MDA		960/50	387 (400-1)	
CIRCLING	1040-1	451 (500-1)	1220-1¾ 631 (700-¾)	1220-2 631 (700-2)

ELEV 589 D TDZE 573

TWR

9021 X 150

7280 X 150

049°

AS

AS

5

23

5

5

REIL Rwy 14, 23 and 32
HIRL Rwy 5-23 and 14-32

TERRE HAUTE, INDIANA
Orig-F 25FEB21

39°27'N-87°18'W

TERRE HAUTE RGNL (HUF')
RNAV (GPS) RWY 5