ILS or LOC RWY 1

AKRON-CANTON RGNL (CAK)

LOC I-CAK	APP CRS	Rwy Ldg	7007
109.5	009°	TDZE	1209
		Apt Elev	1226

** RVR 1800 authorized with the use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1900 then climbing right turn to 3000 direct ACO VOR/DME and hold.

ATIS	CLEVELAND APP CON★	AKRON-CANTON TOWER	GND CON
121.05	125.5 269.25	134.75 279.575	121.7 348.6

ALTERNATE MISSED APCH FIX
KEATN
BSV 15.3
322°
142°
114.05 BSV
R-322
Chan 87(Y)

MISSED APCH FIX
092°
272°
R-092
AKRON
114.4 ACO
Chan 91

KEATN
BSV 15.3

LOCALIZER 109.5
I-CAK

1331±
1377
CABLE
OM
2400
009°
(5)

RADAR REQUIRED

3000
335° (1.7)
(IF)
BULIT
155°
HOLD 3000
335°
R-155
189°

MSA BSV 30 NM
3100

IAF
BRIGGS
114.05 BSV
Chan 87(Y)

ELEV 1226 D TDZE 1209

61
32
7601 X 150
0.6% DOWN
TWR
8204 X 150
0.5% UP
5
009°
HIRL Rwys 1-19 and 5-23

BULIT INT
3000
009°
CABLE OM
2394
2400
GS 3.00°
TCH 53
5 NM
3.5 NM

1900	3000	ACO

CATEGORY	A	B	C	D
S-ILS 1 **	1409/24 200 (200-½)			
S-LOC 1	1600/24 391 (400-½)			1600/40 391 (400-¾)
CIRCLING	1760-1 534 (600-1)		1780-1½ 554 (600-1½)	1800-2 574 (600-2)

FAF to MAP 3.5 NM

Knots	60	90	120	150	180
Min:Sec	3:30	2:20	1:45	1:24	1:10

EC-2, 03 SEP 2026 to 01 OCT 2026
EC-2, 03 SEP 2026 to 01 OCT 2026