

WAAS CH 56331 W04A	APP CRS 043°	Rwy Ldg TDZE Apt Elev	8748 37 40
--	------------------------	-----------------------------	---------------------------------------



RNAV (GPS) RWY 4

Wallops Flight Facility (WAL)

⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Salisbury altimeter setting: increase LPV DA to 342 and all Cats visibility ¼ mile; increase LNAV/VNAV DA to 510 and all Cats visibility ¼ mile; increase all MDA 60 feet and LNAV Cats C/D and Circling Cat C visibility ¼ mile. Baro-VNAV and VDP NA when using Salisbury altimeter setting.

MISSED APPROACH: Climb to 600 then climbing left turn to 2000 direct MAGGO and hold.

ASOS 119.175	PATUXENT APP CON★ 127.95 314.0	Wallops Tower★ 126.5 (CTAF) 306.975 (CTAF)	GND CON 127.875 269.325
------------------------	--	--	-----------------------------------



CATEGORY	A	B	C	D
LPV DA		287-¾	250 (300-¾)	
LNAV/VNAV DA		455-1⅜	418 (500-1⅜)	
LNAV MDA	560-1	523 (600-1)	560-1½	523 (600-1½)
CIRCLING	600-1	560 (600-1)	620-1½ 580 (600-1½)	860-2¾ 820 (900-2¾)

