


VOR/DME RIW 114.05 Chan 87(Y)	APP CRS 101°	Rwy Ldg TDZE 5516 Apt Elev 5516
---	------------------------	---

VOR RWY 10
CENTRAL WYOMING RGNL (RIW)

⚠ When local altimeter setting not received, use Lander altimeter setting and increase all MDA 60 feet and increase S-10 Cat C and D visibility ¼ mile and Circling Cat C visibility ½ mile, increase WUNIB fix minimums Cat C and D visibility ½ mile.
Rwy 10 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 7900 in RIW VOR/DME holding pattern.

ASOS 121.425	SALT LAKE CENTER 133.25 285.6	UNICOM 122.8 (CTAF) 0
------------------------	---	---------------------------------



Remain within 10 NM

PYLOT INT RIW 6.5

7800

7400

*6000

WUNIB RIW 2.2

RIW VOR/DME

4.3 NM

1.4 NM

*6060 when using Lander altimeter setting.

CATEGORY	A	B	C	D
S-10	6000-1	484 (500-1)	6000-1 3/8	484 (500-1 3/8)
CIRCLING	6000-1	484 (500-1)	6000-1 1/2	6120-2 484 (500-1 1/2) 604 (600-2)
WUNIB FIX MINIMUMS (DME REQUIRED)				
S-10	5940-1	424 (500-1)	5940-1 1/4	424 (500-1 1/4)
CIRCLING	6000-1	484 (500-1)	6000-1 1/2	6120-2 484 (500-1 1/2) 604 (700-2)

ELEV 5516

TDZE 5516

REIL Rws 1, 10, and 19 0

MIRL Rwy 1-19 0

HIRL Rwy 10-28 0

NW-1, 03 SEP 2026 to 01 OCT 2026

NW-1, 03 SEP 2026 to 01 OCT 2026