LOC BC RWY 24

DECATUR (DEC)

LOC/DME I-DEC	APP CRS	Rwy Ldg	8496
110.9	240°	TDZE	682
Chan 46		Apt Elev	682

DME required.

When local altimeter setting not received use Lincoln altimeter setting and increase all MDA 80 feet, increase S-LOC 24 Cat C/D visibility ⅛ SM and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH: Climb to 2000 then climbing right turn to 3100 on heading 050° and AXC VORTAC R-348 to MAROA INT/AXC 14.3 DME and hold.

ATIS	CHAMPAIGN APP CON★	DECATUR TOWER★	GND CON	UNICOM
126.35	132.85 290.225	118.9 (CTAF) L 291.775	121.75 291.775	122.95



BACK COURSE

ELEV 682 D TDZE 682



HIRL Rwy 6-24 L
MIRL Rwys 12-30 and 18-36 L

FAF to MAP 3.8 NM					
Knots	60	90	120	150	180
Min:Sec	3:48	2:32	1:54	1:31	1:16



CATEGORY	A	B	C	D
S-LOC 24	1020-1 338 (400-1)			
CIRCLING	1140-1 458 (500-1)	1240-1 558 (600-1)	1360-2 678 (700-2)	1360-2¼ 678 (700-2¼)

EC-3, 03 SEP 2026 to 01 OCT 2026
EC-3, 03 SEP 2026 to 01 OCT 2026