MOLOKAI FIVE DEPARTURE

PAC, 03 SEP 2026 to 29 OCT 2026

TOP ALTITUDE: ASSIGNED BY ATC

RADAR and DME required

HCF APPROACH
124.8 317.6
D-ATIS
127.9 251.15
CLNC DEL
121.4 281.4
GND CON
121.9 348.6
HONOLULU TOWER
118.1 257.8
123.9 273.575 (8R/26L)

TAKEOFF MINIMUMS
Rwys 26L/R: Standard.
Rwys 4L/R: Standard with minimum climb of 425' per NM to 1900, do not exceed 180K until established on assigned heading.
Rwy 8L: Standard with minimum climb of 313' per NM to 1400.
Rwy 8R: Standard with minimum climb of 296' per NM to 500.



NOTE: Departures from Rwys 26L/R must complete left turn to assigned heading within 2 NM of runway departure end (HNL 3 DME). Cross egress fixes at assigned cruising altitude.

NOTE: Departures from Rwys 4L/R and 8L/R must complete right turn to assigned heading within 2 NM of runway departure end. Cross CKH R-240 at or above 2500.

NOTE: REXIE Transition: Expect clearance to ZIGIE then on assigned route.

NOTE: KOLEA Transition: Expect clearance to CLUTS then on assigned route.

NOTE: CODDY Transition: Expect clearance to EBBER or FITES then on assigned route.

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)