MARYSVILLE, CALIFORNIA

RNAV (GPS) RWY 15

APCH CRS	Rwy ldg	12,001
145°	THRE	113
	Arpt Elev	113

(USAF)

BEALE AFB (KBAB)

RNP APCH

* When ALS inop, increase RVR to 60, vis to 1 1/8 miles.
** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile; CAT CDE vis to 1 3/8 miles.
*** Circling not authorized NE of Rwy 15-33.

ALSF-1

MISSED APPROACH: Climb to 3600 direct RADRE, track 145° to ZUTUK, track 105° to RAGTE and hold, continue climb-in-hold to 3600.

ATIS★	NORCAL APP CON	TOWER★	GND CON
124.55 273.5	125.4 259.1	119.4 284.75	121.6 257.75

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 54°C.

9 NM
145°
325°
(IAF)
GGASR
3600
2600
145°
(4.9)
(IF/IAF)
PELAE
1700
(5.9)
(FAF)
PEDCE
255
RW15
370
RADRE
ZUTUK
9 NM
285°
105°
RAGTE
2057
5000
3000
1000

MSA RW15 25 NM
5600

EMERG SAFE ALT 100 NM 13,700

VGSI and RNAV glidepath not coincident (VGSI Angle 2.75/TCH 53).

3600	RADRE	tr 145°	ZUTUK

PELAE
2600
145°
PEDCE
1700
1.5 NM to RW15
RW15
GP 2.75°
TCH 47
5.3 NM

ELEV 113
THRE 113
145°
15
BCN
240
12,001 x 300
TWR
274
33
HIRL all rwys

CATEGORY	A	B	C	D	E
LNAV/VNAV DA*	530/40		417	(500-¾)	
LNAV MDA**	600/24	487 (500-½)	600/50	487	(500-1)
CIRCLING***	600-1	487 (500-1)	600-1½ 487 (500-1½)	800-2¼ 687 (700-2¼)	800-2½ 687 (700-2½)

SW-2, 03 SEP 2026 to 01 OCT 2026
SW-2, 03 SEP 2026 to 01 OCT 2026