

WAAS CH 99335 W30A	APP CRS 301°	Rwy Ldg 3998 TDZE 2206 Apt Elev 2209
--	------------------------	---

RNAV (GPS) RWY 30

PHILIP (PHP)



▼

⚠

DME/DME RNP-0.3 NA. When local altimeter setting not received, use Pierre altimeter setting and increase all DA 204 feet and MDA 220 feet and increase LPV all Cats visibility ½ mile, increase LNAV/VNAV all Cats visibility 1 mile, increase LNAV Cat C visibility ½ mile, and increase Circling Cat C visibility ¾ mile. Helicopter visibility reduction below 1 SM NA. Procedure NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 54°C (130°F). Baro-VNAV NA when using Pierre altimeter setting.

MISSED APPROACH:
Climb to 4500 direct
CUSED and hold.

ASOS 118.375	DENVER CENTER 127.95 338.2	UNICOM 122.8 (CTAF) 0
------------------------	--------------------------------------	---------------------------------



4500 CUSED		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 27).		5 NM Holding Pattern
HUVBI 3800		RW30 3800		GP 3.00° TCH 40
4.9 NM		7 NM		
CATEGORY	A	B	C	D
LPV DA	2456-1	250 (300-1)	2456-1 3/8 250 (300-1 3/8)	NA
LNAV/VNAV DA	2794-2		588 (600-2)	NA
LNAV MDA	2620-1	414 (500-1)	2620-1 1/4 414 (500-1 1/4)	NA
CIRCLING	2720-1 511 (600-1)	2760-1 551 (600-1)	2840-1 3/4 631 (700-1 3/4)	NA