

NDB MF

372

APP CRS

322°

Rwy Ldg

9001

TDZE

1293

Apt Elev

1297

NDB RWY 32

MANSFIELD LAHM RGNL (MF'D)

RADAR required for procedure entry.

For inop ALS increase Cats A and B visibility to RVR 5500.

MALS

AS

MISSED APPROACH: Climb to 2300 then climbing right turn to 3000 direct MF NDB and hold.

ATIS	CLEVELAND APP CON ★	MANSFIELD TOWER ★	GND CON	UNICOM
125.3	128.35 360.65	119.8 (CTAF) 291.775	121.8 291.775	122.95

ELEV 1297

D

TDZE 1293

5

23

32

0.9% UP

8001 X 130

8819 X 150

TWR

AS

322°

HIRL Rwys 5-23 and 14-32

REIL Rwys 5 and 23

FAF to MAP 4 NM

Knots	60	90	120	150	180
Min:Sec	4:00	2:40	2:00	1:36	1:20

2300

3000

MF

MF NDB

Remain within 10 NM

142°

2900

322°

2700

3.18°

TCH 50

4 NM

CATEGORY	A	B	C	D
S-32	1820/40	527 (600-¾)	1820/55	527 (600-1)
CIRCLING	1820-1	523 (600-1)	2000-2 703 (800-2)	2000-2¼ 703 (800-2¼)

MANSFIELD, OHIO

Amdt 12 02OCT25

40°49'N-82°31'W

MANSFIELD LAHM RGNL (MF'D)

NDB RWY 32

EC-2, 03 SEP 2026 to 01 OCT 2026

EC-2, 03 SEP 2026 to 01 OCT 2026