

WAAS CH 42700 W28A	APP CRS 281°	Rwy Ldg TDZE Apt Elev	6003 85 85
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 28


MILLVILLE MUNI (MIV)

RNP APCH-GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use ACY altimeter setting: increase LPV DA to 400 feet; increase LNAV/VNAV DA to 461 feet; increase all MDAs 60 feet and LNAV and Circling visibility Cat C ½ SM. Baro-VNAV and VDP NA when using ACY altimeter setting.

MISSED APPROACH: Climb to 2000 direct TIYDU and right turn on track 030° to RUPDE and right turn 077° track to VCN VOR/DME and hold.

ASOS 119.6	ATLANTIC CITY APP CON 124.6 327.125	UNICOM 123.0 (CTAF) 0
----------------------	---	---------------------------------



ELEV 85	TDZE 85
---------	---------

2000 TIYDU

tr 030° RUPDE

tr 077° VCN

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/ TCH 29)

CROSE

NENYI

1.7 NM to RW28

281° 2000

GP 3.00° TCH 45

CATEGORY	A	B	C	D
LPV DA	344-1 259 (300-1)			
LNAV/ VNAV DA	405-1 320 (400-1)			
LNAV MDA	640-1 555 (600-1)		640-1½ 555 (600-1½)	640-1¾ 555 (600-1¾)
CIRCLING	640-1 555 (600-1)		660-1½ 575 (600-1½)	660-2 575 (600-2)