

LOC I-AYS 108.3	APP CRS 184°	Rwy Ldg 5992 TDZE 140 Apt Elev 141
---------------------------	------------------------	---

ILS Y or LOC Y RWY 19

WAYCROSS-WARE COUNTY (AYS)

GPS required. When local altimeter setting not received, use Alma altimeter setting: increase DA to 390 feet and all MDA 60 feet; increase S-LOC 19 Cat C/D visibility 1/8 mile; increase Circling Cat C/D visibility 1/4 mile. For inop MALSRS when using Alma altimeter setting, increase S-LOC 19 Cat C/D visibility to 1 1/8 mile. Night landing Rwy 5, 31 NA.

MALSRS

MISSED APPROACH:
Climb to 1800 direct
BAQAV and hold.

AWOS-3 118.575	JACKSONVILLE CENTER 127.575 269.025	UNICOM 122.8 (CTAF) 1
--------------------------	---	---------------------------------

30 NM to BUUV (NoPT)
2300
9 NM to BUUV
1700
BUUV

094° 274°

094° 004°

FEVAL

30 NM to FEVAL

2300

WAYCROSS
112.4 AYS
Chan 71

LOCALIZER 108.3
I-AYS

GPS or RADAR REQUIRED

004° 184° 004°
4 NM
1700 NoPT (8)
1700 NoPT (8)
(IF/IAF) BUUV INT
(FAF) AGLUY INT
AY OM
R-039
R-064

004° 274°
HULEG
30 NM to HULEG
2100

ELEV 141 TDZE 140

184°

219 5 31

5992 X 100 5044 X 100 3554 X 75

HIRL Rwy 1-19
REIL Rwy 19

FAF to MAP 4.7 NM

Knots 60 90 120 150 180
Min:Sec 4:42 3:08 2:21 1:53 1:34

1800 BAQAV

AGLUY 1700
BUUV 1700
4 NM Holding Pattern
004° 1700 184°
GS 3.00° TCH 51
VGSi and ILS glidepath not coincident (VGSi Angle 3.00/TCH 45).

4.7 NM 6 NM

CATEGORY	A	B	C	D
S-ILS 19	340-1/2 200 (200-1/2)			
S-LOC 19	600-1/2	460 (500-1/2)	600-7/8	460 (500-7/8)
CIRCLING	660-1 519 (600-1)	720-1 579 (600-1)	860-2 719 (800-2)	860-2 1/4 719 (800-2 1/4)

WAYCROSS, GEORGIA

Waycross-ware County (AYS)

Orig 04FEB16

31°15'N-82°24'W

ILS Y or LOC Y RWY 19