


LOC I-YAK	APP CRS	Rwy Ldg	7732
111.1	115°	TDZE	40
		Apt Elev	40


ILS or LOC RWY 11

YAKUTAT (YAK) (PAYA)

DME required.	MALSR	MISSED APPROACH: Climb to 1000 then climbing right turn to 2400 direct YAK VOR/DME and hold, continue climb-in-hold to 2400.
Circling Rwy 20 NA at night. When Yakutat altimeter setting not received, procedure NA. DME from YAK VOR/DME. DME use requires simultaneous reception of I-YAK and YAK DME.		

ASOS 135.75	ANCHORAGE CENTER 119.0 263.1	JUNEAU RADIO 123.6 (CTAF) 0
----------------	---------------------------------	--------------------------------



 1000 2400 HEJNO YAK 17 ADKUH YAK 4.2 FETOB YAK 2.1 YAK 1.6 1800 1300 640 GS 3.00° TCH 53 12.8 NM 2.1 NM 0.5 1.2 NM				
CATEGORY	A	B	C	D
S-ILS 11	240/24 200 (200-½)			
S-LOC 11	480/24	440 (500-½)	480/40	440 (500-¾)
CIRCLING	520-1 480 (500-1)	540-1 500 (500-1)	820-2¼ 780 (800-2¼)	820-2½ 780 (800-2½)

