

LOC/DME I-AKN 110.3 Chan 40	APP CRS 121°	Rwy Ldg 8500 TDZE 62 Apt Elev 73
---	------------------------	---

ILS Y or LOC Y RWY 12
KING SALMON (AKN)(PAKN)

DME required.


- V** Autopilot coupled approach NA below 700. Inop table does not apply.
A When local altimeter setting not received, use WSN/PFWs altimeter setting and increase S-ILS 12 DA to 301 feet; increase all MDAs 40 feet. For inop ALS when using WSN/PFWs altimeter setting increase S-LOC 12 Cat C/D/E visibility to RVR 6000. Inop table does not apply when using WSN/PFWs altimeter setting to S-ILS 12 all Cats and S-LOC 12 Cat A and B.

MALSR



MISSED APPROACH: Climb to 600 then climbing right turn to 3000 on heading 240° and AKN VORTAC R-210 to OLLER/AKN 15 DME and hold.

ATIS 128.8	ANCHORAGE CENTER 124.8 354.0	KING SALMON TOWER* 118.3 279.5	GND CON 121.9	UNICOM 122.95	CTAF 121.9 352.05
---------------	---------------------------------	-----------------------------------	------------------	------------------	----------------------



Use I-AKN DME when on the localizer course.

Remain
within 15 NM

2000

GS 3.00°
TCH 66

1700

CATEGORY

A

B

C

D

E

S-ILS 12

262/50 200 (200-1)


S-LOC 12

420/50 358 (400-1)

FLEV 73

D

TDZE 62

MIRL Rwy 18-36 HIRL Rwy 12-30 **L**