

TACAN Z RWY 32

TACAN EIL Chan 98	APCH CRS 325°	Rwy lgt 14,529 TDZE 548 Arprt Elev 548	[USAF]	EIELSON AFB (PAEI)	
DME or RADAR required. RADAR required b/n FALCO-WAKOV.			ALSIF-1	MISSED APPROACH: Climbing left turn on EIL R-254 to 4000 to WAKOV and hold. Continue climb-in-hold.	
* When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1 1/8 mile.					
ATIS ★ 119.9 273.5	FAIRBANKS APP CON 127.1 251.1 (360°- 179°) 125.35 363.2 (180°- 359°)	TOWER ★ 127.2 352.05	GND CON 121.8 275.8		
** Circling not authorized E of Rwy 14-32.					
EMERG SAFE ALT 100 NM 16,000'					
ELEV 548	TDZE 548	WAKOV EIL 14			
Rwy lgt on N 11,314' of rwy 300' wide, rwy lgt on S 3200' of rwy 150' wide.					
HIRL Rwy 14-32					
CATEGORY	A	B	C	D	E
S-32 *	1040/24 492 (500-1/2)		1040/50 492 (500-1)		
CIRCLING **	1040-1 492 (500-1)		1040-1 1/2 492 (500-1 1/2)	1280-2 1/4 732 (800-2 1/4)	1280-2 1/2 732 (800-2 1/2)