

WAAS CH 90202 W13A	APP CRS 133°	Rwy Ldg 9033 TDZE 1280 Apt Elev 1317
--	------------------------	---

RNAV (GPS) RWY 13
ROCHESTER INTL (RST)

RNP APCH - GPS.

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to RVR 5500.

MALSR




MISSED APPROACH: Climb to 2900 direct POKYI and on track 241° to RST VOR/DME and hold.


ATIS 120.5	ROCHESTER APP CON★ 119.8 251.125	ROCHESTER TOWER★ 118.3 (CTAF) 0 257.8	GND CON 121.9	UNICOM 122.95
----------------------	--	---	-------------------------	-------------------------

Procedure NA for arrivals at CORDY
on V82-161 northwest bound.

Procedure NA for arrivals at FISIN
on V218 northwest bound.



VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 53).



CATEGORY	A	B	C	D
LPV DA	1530/18 250 (300-½)			
RNAV/ VNAV DA	1679/50 399 (400-1)			
RNAV MDA	1640/24 360 (400-½)	1640/30 360 (400-½)	1640/50 360 (400-1)	
CIRCLING	1720-1 403 (500-1)	1780-1 463 (500-1)	1900-1½ 583 (600-1½)	1900-2 583 (600-2)

