

WAAS CH 56303 W02A	APP CRS 021°	Rwy Ldg 8000 TDZE 867 Apt Elev 871
--	------------------------	---

RNAV (GPS) RWY 2

CENTRAL IL RGNL/BLOOMINGTON-NORMAL (BMI)

RNP APCH - GPS.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. Baro-VNAV and VDP NA when using PIA altimeter setting. Inop table does not apply to LPV. For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 6000 and LNAV Cats C and D visibility to RVR 6000. When local altimeter setting not received, use PIA altimeter setting: increase LPV DA to 1183 feet; increase LNAV/VNAV DA to 1376 feet and all Cats visibility to RVR 5500; increase all MDAs 120 feet and Circling visibility Cats C and D ¼ SM. For inop ALS when using PIA altimeter setting; increase LNAV/VNAV all Cats visibility to 1 ½ SM and increase LNAV Cats C and D visibility to 1 ¾ SM.

MALS

A5

MISSED APPROACH:
Climb to 3000 direct ZEMEN and on track 335° to KAPPA and hold, continue climb-in-hold to 3000.

ATIS

119.575

SAINT LOUIS APP CON

128.725 256.9

BLOOMINGTON TOWER ★

124.6 (CTAF) 269.575

GND CON

121.65

UNICOM

122.95

